



Spécifications Techniques

System

Product name	IPEVO TOTEM 180
Model	CDCU-02IP
Part number	5-910-2-08-00
CPU	Novatek NT96685T
Flash	2Gb
RAM	4Gb

Camera

Sensor	2 x 1/3" CMOS sensor
Max resolution	4640x1456
Lens type	Fixed focus
Focal length	2.3mm
Aperture	
Iris type	
FOV	Horizontal:180° Vertical: 56.5°
Shutter time	1/30~1/4000 sec
WDR	
Minimum illumination	
Tilt range	±6°
Zoom	ePTZ, 5X digital zoom

Video

Video compression	H.264 MJPG NV12
Max frame rate	4640x1456 (30p) (Panorama) 3520x1104 (30p) 1920x1080 (30p) 1280x720 (30p) 640x360 (30p)

System requirements

Operating system	Mac: Minimum: Intel® Core™ i5 CPU 1.8 GHz or higher, OS X 10.10 or higher, 2 GB RAM, 256MB of dedicated video memory (For lag-free live streaming up to 1920 x 1080) Recommended: Intel® Core™ i5 CPU 2.5 GHz or higher, OS X 10.14 or higher, 8GB RAM, Solid-state drive, 256MB of dedicated video memory (For lag-free live streaming up to 1920 x 1080, and video recording of 1920 x 1080)
	Windows: Minimum: Microsoft Windows 7 Service Pack 1 or higher, Intel® Core™ i3 CPU 3.20 GHz or higher, 4 GB RAM, 256MB of dedicated video memory (For lag-free live streaming up to 1920 x 1080) Recommended: Microsoft Windows 10, Intel® Core™ i5 CPU 3.40 GHz or higher, 8GB RAM, 256MB of dedicated video memory (For lag-free live streaming up to 1920 x 1080, and video recording of 1920 x 1080) Chromebook : Chromebooks with a USB Type-C port

In the Package

Packing contents	Quick installation guide 1.8m USB-C cable IPEVO TOTEM 180
------------------	-----------------------------------------------------------------

Audio

Microphone

Microphone type	2 x Omni-directional microphones
Audio compression	PCM
Voice pick up range	5m
S/N Ration	50dB
Frequency range	100Hz to 8KHz

Audio quality

Noise reductionEcho cancellation

General

Connector	USB-C 3.0
LED indicator	180/120° status Auto framing statusmute/unmute
Power input	DC 5V / 1.5A (USB - C connector)
Power consumption	5V / 1.2 ~ 1.3A
Dimension	66 x 72 x 264 mm (216.5 x 236 x 866 ft)
Wight	370g (0.82lb)
UVC	Yes
UAC	Yes

Environment

Operating temperature	0°C to 40°C
Storage temperature	-10°C to 50°C
Humidity	10% to 95%