



SFP Transceivers

D-Link Gigabit Interface Converters are transceivers that connect Gigabit switches and 10/100Mbps switches with GBIC slots to Gigabit Ethernet networks, providing high-speed connections over the fiber-optic or twisted-pair cable. The fiber-optic transceivers have standard duplex LC connectors for connection compatibility.

Small Form Pluggable (SFP) Package

These transceivers use the industry-standard Small Form Pluggable (SFP) package. They slide into the mini GBIC slot of the Gigabit device. They provide the necessary signal amplification for data to be transmitted to the network cable from the port, and vice versa, for the port to receive data from the network cable.

Hot Swappable

All D-Link Mini GBIC transceivers are hot-swappable. You can remove or replace the GBIC transceiver with the system powered on. This permits modules and mini-GBICs to be added or swapped without interrupting the network.

Applications

Applications of the fiber transceivers include distributed multi-processing, Gigabit switch cascading, high-speed I/O file transfer, bus extension application, and channel extender/data storage.

Single-mode Fiber Transceiver (10 km)

DEM-310GT

- 1000BASE-LX port (IEEE 802.3z standard)
- Duplex LC connector
- Full duplex operation
- 802.3x flow control support
- Fiber type: 9um single-mode fiber up to 10 km
- Wave length: 1310nm
- Power support: 3.3V
- Power budget: 10.5dB
- Hot pluggable
- Class 1 laser product complies with EN 60825-1
- TTL signal detect indicator
- Metal enclosure for lower EMI

Multi-mode Fiber Transceiver (550 m)

DEM-311GT

- 1000BASE-SX port (IEEE 802.3z standard)
- Duplex LC connector
- Full duplex operation
- 802.3x flow control support
- Fiber type: 50um or 62.5um multi-mode fiber up to 550 m
- Wave length: 850nm
- Power support: 3.3V
- Hot pluggable
- Class 1 laser product complies with EN 60825-1
- TTL signal detect indicator
- Metal enclosure for lower EMI

Single-mode Fiber Transceiver (50 km)

DEM-314GT

- 1000BASE-LX port (IEEE 802.3z standard)
- Duplex LC connector
- Very low jitter
- Full duplex operation
- 802.3x flow control support
- Fiber type: 9/125um single-mode fiber up to 50 km
- Wave length: 1310nm
- Power supply: 3.3V
- Power budget: 22dB
- Hot pluggable
- Class 1 laser product complies with EN 60825-1
- TTL signal detect indicator
- Metal enclosure for lower EMI

Single-mode Fiber Transceiver (80 km)

DEM-315GT

- 1000BASE-LX port (IEEE 802.3z standard)
- Duplex LC connector
- Very low jitter
- Full duplex operation
- 802.3x flow control support
- Fiber type: 9/125um single-mode fiber up to 80 km
- Wave length: 1550nm
- Power supply: 3.3V
- Power budget: 22dB
- Low power dissipation <700mW
- Hot pluggable
- Class 1 laser product complies with EN 60825-1
- TTL signal detect indicator
- Metal enclosure for lower EMI

Transceiver

Physical & Environmental

Operating Temperature

0° to 50 °C

Storage Temperature

-25° to 55 °C

Humidity

5% to 95% non-condensing

Ordering Information

SFP Transceiver

DEM-310GT	For 1000BASE-LX, single-mode fiber, 10 km max., 3.3V
DEM-311GT	For 1000BASE-SX, multi-mode fiber, 550 m max., 3.3V
DEM-314GT	For 1000BASE-LX, single-mode fiber, 50 km max., 3.3V
DEM-315GT	For 1000BASE-LX, single-mode fiber, 80 km max., 3.3V



Specifications subject to change without prior notice. D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.	U.S.A Canada Europe (U. K.) Germany France Netherlands Belgium Italy Sweden Denmark Norway Finland Spain Portugal Czech Republic Switzerland Greece Luxemburg Poland Hungary Singapore Australia India Middle East (Dubai) Turkey Egypt Israel LatinAmerica Brazil South Africa Russia China Taiwan Headquarters	TEL: 1-800-326-1688 TEL: 1-905-8295033 TEL: 44-20-8731-5555 TEL: 49-6196-77990 TEL: 33-1-30238688 TEL: 31-10-282-1445 TEL: 32(0)2-517-7111 TEL: 39-02-2900-0676 TEL: 46-(0)8564-61900 TEL: 45-43-969040 TEL: 47-99-300-100 TEL: 358-9-2707 5080 TEL: 34-93-4090770 TEL: 351-21-8688493 TEL: 420-(603)-276-589 TEL: 41-(0)-1-832-11-00 TEL: 30-210-9914 512 TEL: 32-(0)2-517-7111 TEL: 48-(0)-22-583-92-75 TEL: 36-(0)-1-461-30-00 TEL: 65-6774-6233 TEL: 61-2-8899-1800 TEL: 91-022-26526696 TEL: 971-4-3916480 TEL: 90-212-289-56-59 TEL: 202-414-4295 TEL: 972-9-9715700 TEL: 56-2-232-3185 TEL: 55-11-218-59300 TEL: 27-12-665-2165 TEL: 7-095-744-0099 TEL: 86-10-58635800 TEL: 886-2-2910-2626 TEL: 886-2-2916-1600	FAX: 1-866-743-4905 FAX: 1-905-8295223 FAX: 44-20-8731-5511 FAX: 49-6196-7799300 FAX: 33-1-30238689 FAX: 31-10-282-1331 FAX: 32(0)2-517-6500 FAX: 39-02-2900-1723 FAX: 46-(0)8564-61901 FAX: 45-43-424347 FAX: 47-22-309580 FAX: 358-9-2707-5081 FAX: 34-93-4910795 FAX: 41(0)-1-832-11-01 FAX: 30-210-9916902 FAX: 32-(0)2-517-6500 FAX: 48-(0)-22-583-92-76 FAX: 36-(0)-1-461-30-09 FAX: 65-6774-6322 FAX: 61-2-8899-1868 FAX: 91-022-26528914 FAX: 971-4-3908881 FAX: 90-212-289-76-06 FAX: 202-415-6704 FAX: 972-9-9715601 FAX: 56-2-232-0923 FAX: 55-11-218-59322 FAX: 27-12-665-2186 FAX: 7-095-744-0099 #350 FAX: 86-10-58635799 FAX: 886-2-2910-1515 FAX: 886-2-2914-6299
---	---	---	--